

Amwell Systems Ltd  
 Ground Floor, Suite 2  
 Middlesex House  
 Meadway Corporate Centre  
 Stevenage, Herts  
 SG1 2EF

T: 01763 276200 F: 01763 276222  
 Email: [contact@amwell-systems.com](mailto:contact@amwell-systems.com)  
 Web: [www.amwell-systems.com](http://www.amwell-systems.com)

## K32 PANEL CUBICLES

### 120 PANEL CUBICLES – UNFRAMED

<b>Product Reference:</b>	<b>‘Sylan Pivot’</b> toilet cubicles – <b>Glass.</b>
<b>Doors/Pilasters:</b>	36mm MDF core faced on both sides with high pressure laminate, long edges rebated to facilitate the outside face of the door to close flush with the outside face of the pilaster.
<b>Base Colour:</b>	AM269 Linen or AM275 Charcoal depending on glass colour.
<b>Edge Treatment:</b>	All edges finished in ColourCoat to match glass option.
<b>Surface:</b>	4mm thick double back painted toughened safety glass.
<b>Surface Colour:</b>	Amwell Black or Amwell White.
<b>Divisions:</b>	36mm MDF core faced on both sides with high pressure laminate.
<b>Colour:</b>	AM269 Linen or AM275 Charcoal depending on glass colour.
<b>Edge treatment:</b>	Lipped with 0.6mm PVC with AM269 Linen or AM275 Charcoal depending on glass colour.
<b>Surface:</b>	4mm thick double back painted toughened safety glass.
<b>Colour:</b>	Amwell Black or Amwell White.
<b>Fixing Details:</b>	Invisible division to pilaster fixings. Aluminium headrail powder coated gloss white or black to suit glass or Satin anodised aluminium to suit other fixtures. Discreet satin anodised aluminium gravity channel for divisions to wall fixing and wall end pilaster fixing. All glass will be supplied loose and is to be fitted on site.
<b>Ironmongery/Accessories:</b>	Self-closing and dampened pivot hinge system. Buffered coat hook. Mortice lock machined flush into door and pilaster rebates, complete with DDA compliant lever-operated indicator bolt with circular face plate incorporating emergency release facility.

# Sylan



**Finish/Colour:** Stainless Steel.

**Dimensions:** 2060mm - 2700mm overall height including 20mm floor clearance.  
(Please note maximum depth of division is 1500mm for heights over 2400mm).

**Other requirements:** Where detailed on drawings outward opening doors have been allowed complete with polished aluminium pull handles to the outside face of door.