



Sylan Ground Floor, Suite 2 Middlesex House Meadway Corporate Centre Stevenage, Herts SG1 2EF T: 01763 276200 contact@sylan-washrooms.uk www.sylan-washrooms.uk

## **K32 PANEL CUBICLES**

## 120 PANEL CUBICLES – UNFRAMED

Product Reference:	'Sylan Pivot' toilet cubicles – Glass.
Doors/Pilasters:	35mm MDF core faced on both sides with high pressure laminate and cladded with glass, long edges rebated to facilitate the outside face of the door to close flush with the outside face of the pilaster.
Base Colour:	TA352 Salt or TA337 Black depending on glass colour.
Edge Treatment:	Lipped with matching ABS
Surface:	4mm thick double back painted toughened safety glass.
Colour:	Black or White.
Divisions:	25mm MDF core faced on both sides with high pressure laminate and cladded in glass.
Colour:	TA352 Salt or TA337 Black depending on glass colour.
Edge treatment:	Lipped with matching ABS.
Surface:	4mm thick double back painted toughened safety glass.
Colour:	Black or White.
Fixing Details:	Invisible division to pilaster fixings. Aluminium headrail pow

Invisible division to pilaster fixings. Aluminium headrail powder coated gloss white or black to suit glass or Satin Anodised

Aluminium to suit other fixtures. Discreet Satin Anodised Aluminium gravity channel for divisions to wall fixing and wall end pilaster fixing. All glass will be supplied loose and is to be

fitted on site.

**Ironmongery/Accessories:** Self-closing and dampened pivot hinge system. Buffered coat

hook.

Mortice lock machined flush into door and pilaster rebates, complete with DDA compliant lever-operated indicator bolt





with circular face plate incorporating emergency release  $% \left( \mathbf{r}\right) =\left( \mathbf{r}\right)$ 

facility.

**Standard Dimensions:** Up to 2600mm maximum overall height including 20mm floor

clearance (to doors/fronts only) and 40mm headrail, 20mm ceiling clearance required for headrail installation. Divisions 2000mm deep. Additional heights achievable subject to specific

project review.

Other requirements: Where detailed on drawings outward opening doors have been

allowed complete with polished aluminium pull handles to the

outside face of door.