K32 Panel cubicles/ duct and wall linings/ screens

To be read with Preliminaries/General conditions

## 120/01

## PANEL CUBICLES - UNFRAMED

Drawing reference(s):

- Manufacturer and reference: Venesta Washroom Systems, 1st Floor, Units 19-23 | St George's Square, St George's Shopping Centre, Gravesend, Kent, DA11 0TA. Tel 01474 353333.
- Product: 'Sahara ColourCoat High Gloss' range.
- Board/panel type: High performance Medium Density 720kg/m<sup>3</sup> grade Fibreboard (MDF).
- Finish: Sprayed with one coat of primer and finished with 80% gloss pigmented polyurethane lacquer.
- Edge treatment: Sprayed with one coast of primer and finished with 80% gloss pigmented polyurethane lacquer.
- Thickness: Partitions 26mm nominal thickness with MDF core. Doors 36mm nominal thinckness with MDF core.
- Pilasters: Satin anodised aluminium extrusions.
- Depth: 2086mm maximum recommended from face of back wall or rear ducting.
- Floor clearance: 100mm as standard (see options below).
- Ceiling clearance: Minimum 20mm above headrail.
- Pedestal adjustment: +10mm.
- Range height: 2139mm including floor clearance.
- Headrail: 40mm thick slimline satin anodised aluminium profile, to finish 20mm below ceiling height.
- Hinges: Floating soft self closing stainless steel pilaster mounted pivot hinges (supplied as an assembly).
- Pedestals: 100mm stainless steel modular pedestal as standard (see options below).
- Indicator bolt: Stainless steel modular flip style indicator bolt with mortice lock. Stainless steel circular face plate with unique emergency release facility.
- Wall fixings: Z-clip and gravity channel fixing
- Colour/finish: From Venesta's standard RAL classic colour range.
- Optional accessories: Venesta toilet roll holder (NBS Clause N13/462); Venesta coat hook (NBS Clause N13/429); Document M 2004 compliant grab rails and door pulls (NBS Clause N13/436).

## Pedestal height options:

- *50mm*
- 100mm
- 150mm
- 230mm (for export only)